

Instructiuni update Sunny V35

ATENTIE!Inainte de a incepe procedura de update, asigurati-va ca ati citit si inteles bine instructiunile, ca
aveti toate cele necesare pentru a avea o instalare in conditii optime. Daca nu sunteti siguri ca
puteti instala softul NU O FACETI! Puteti intra in contact cu un reprezentant tehnic la adresa de
mail: support@e-boda.ro, pentru a primi mai multe detalii despre procedura de update.ATENTIE!Daca pe perioada rescrierii de soft blocati tableta nerespectand procedura de update detaliata mai
jos si doriti ca Departamentul Service sa o repuna in functiune va trebui sa suportati costurile de
transport catre si dinspre unitatea de Service (costuri de curier), iar interventia se va face gratuit.
Desi tableta va ramane in garantie, aceasta operatiune nu se va incadra in regulile legale de
garantie din punctul de vedere al duratei de solutionare. In acest caz solutionarea poate dura pana
la 30 de zile calendaristice.Utilizatorii produselor E-Boda au creat un forum dedicat tabletelor. Desi acesta nu este un forum
oficial si nu ne asumam nici un fel de responsabilitate pentru continut, va recomandam sa cititi
sectiunea cu referinta la modelul Dvs. de unde veti obtine informatii despre utilizarea acestuia,

tricks and tips, software homemade, etc.

Procedura update:

- ► Descarcati de pe site-ul <u>www.e-boda.ro</u> ultima actualizare software.
- Dupa ce ati downloadat versiunea de soft dorita, pe PC va trebui sa dezarhivati continutul.
- ► Faceti backup tuturor datelor importante. Procedura de update sterge memoria interna a telefonului.
- ► Asigurati-va ca bateria este incarcata mai mult de 70% (va recomandam sa incarcati bateria pana la 100% inainte de a incepe procedura de update).
- ▶ Opriti temporar programul antivirus al calculatorului inainte de a incepe procedura pentru update.

1. Introduceti Cablul USB in oricare din porturile USB 2.0 ale PC-ului,

NOTA Pentru buna desfasurare a procedurii de update, folositi un port USB 2.0 al PC-ului.

2. Conectati Cablul USB la telefon (cu telefonul pornit),

3. Asteptati pana ce driverul va fi instalat automat. In cazul in care driverul nu se va instala automat (in functie de sistemul de operare al PC-ului), deschideti folderul "Driver_V35_Auto_Installer" (folderul poate fi gasit in arhiva "SP_Flash_Tool_v3.1312.0.139_and_driver_V35"), faceti click x2 pe "V35 Driver.exe" si asteptati finalizarea instalarii driverului,

4. Deconectati telefonul de la Cablul USB,

5. Opriti telefonul,



6. Porniti "Flash_tool.exe" Flash_tool (icoana acestui program pentru update poate fi gasita in folderul "SP_Flash_Tool_v3.1312.0.139"),

4. Apasati butonul "Scatter-loading" pentru adaugarea noului Firmware,

🔓 Smart Phone Fl	lash Tool (Runtime Trace	Mode)				
File Action Op	otions Window Help					
Download Read b	oack Memory Test					
😳 Format	😋 Firmware -> Upgrade	C≇ Download	Ø Stop	🗖 DA DL /	All With Check Sum	
Download Agent	D:\	\SP_Flash_T	ool_v3.1312.0.1	139\MTK_AllInO	ne_DA.bin	🕞 Download Ager
Scatter-loading File						🗁 Scatter-loading
Authentication File						🗁 Auth File
Certification File						🗁 Cert File
Nand Util File						🕞 Nand Util File
•			III			
				0%		
	NAND	USB 921	600 bps			
		DA DL All Without	Battery (Full S	peed)		

5. Selectati noul Firmware asa cum este aratat in imaginea de mai jos,

Smart Phone Flash T	Copen Scatter	file				x	
Download Read back	Look in:	→ ++++¦μ +		•	🗢 🗈 💣 📰 🔻		
0	Ca	Name	*		Date modified	Туре	
Format Firm		android	info		01-Jul-13 17:25	TXT File	
Download Agent D:\K	Recent Places	installed	-files		01-Jul-13 17:55	TXT File	🕒 Download Agent
Scatter-loading File		MT6577	_Android_scatter_en	nmc	01-Jul-13 17:22	TXT File	- 🕞 Scatter-loading
Authentication File	Desktop						Auth File
Certification File							Cert File
land Util File	Libraries						🗁 Nand Util File
name							
	Computer						
	Network						
		•	i i i i i i i i i i i i i i i i i i i	11		•	
		File name:	MT6577_Andro	d_scatter_emmc	•	Open	
		Files of type:	Map File (*.txt)			Cancel	
4		-	m	_			
				0%			
	NAND	USB	921600 bps				
		DA DL All With	out Battery (Full Sp	eed)			



6. Apasati butonul "Firmware -> Upgrade",

Smart Phone F	lash Tool (Runtime Trace Mode)	
File Action Op Download	ptions Window Help	
© Format	Eirmware -> Upgrade Download Stop DA DL All With 0	heck Sum
Download Agent	D:\ \SP_Flash_Tool_v3.1248.0.96 (Pentru V100)\MTK_A	IIInOne_DA.bin 🕞 Download Agent
Scatter-loading File	D:\ \6. (14.06.2013)\S8073B_MP_F2F3F8_B1B8_R0_B0D_04_06_	flasher_user\MT6577_Android_scatter.
Authentication File	,	🕞 Auth File
Certification File		🕞 Cert File
Nand Util File		🕞 Nand Util File
name	region address begin address end address location	
PRELUADER DSP_BL DSP_BL MBR EBR1 UB00T B00TIMG RECOVERY SEC_R0 LOG0 ANDROID A	0x00000000 0x00000000 0x00000000 0x1TELEFDANE 0x100x1 0x000000000 0x000000000 0x000000000 D:\TELEFDANE 0x100x1 0x000000000 0x000000000 D:\TELEFDANE 0x100x1 0x1 0x000000000 0x000000000 D:\TELEFDANE 0x100x1 0x1 0x000000000 0x000000000 D:\TELEFDANE 0x100x1 0x1 0x000000000 0x00000000 D:\TELEFDANE 0x100x1 0x1 0x000000000 0x00000000 0x00000000 D:\TELEFDANE 0x1 0x000000000 0x000000000 0x00000000 D:\TELEFDANE 0x1 0x0000000000 0x000000000 0x1 D:\TELEFDANE 0x1 0x0000000000 0x000000000 0x1 D:\TELEFDANE 0x1 0x000000000 0x000000000 0x1 D:\TELEFDANE 0x1 0x000000000 0x000000000 0x1 D:\TELEFDANE 0x1 0x000000000 0x0000000000	L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_fit L06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_
	0%	
S	NAND USB 921600 bps	
	DA DL All Without Battery (Full Speed)	

7. Introduceti cablul USB conectat la PC in telefon, procesul de update va porni automat,

NOTA In cazul in care procesul de update nu va incepe automat, scoateti cablul USB din telefon si repetati pasii mentionati mai sus.

8. La aparitia icoanei "Firmware Upgrade ...", puteti deconecta cablul USB introdus in telefon (priviti imaginea de mai jos),



Download Read back Memory Test Format Firmware > Upgrade Download Stop DA DL All With Check Sum Download Agent D:\ \SP_Flash_Tool_v3.1248.0.96 (Pentru V100)\MTK_AllInOne_DA.bin Download Agent Scatter-loading File D:\ \Sc (14.06.2013)\S80738_MP_F2F3F8_B1B8_R0_B0D_04_06[flasher_user\MT6577_Android_scatter. Download Agent Variation File Firmware Upgrade Timware Upgrade Timware Upgrade Download Vand Util File Firmware Upgrade Download Agent Scatter-Ioa Auth File Vand Util File Firmware Upgrade Timware Upgrade Download Download Agent Vand Util File Download Agent 0x00000000 0x00000000 Download Agent Download Agent Download Agent Vand Util File Firmware Upgrade Timware Upgrade Timware Upgrade Timware Upgrade Download Agent Downlo	File Action Op	tions Window He	lp					
Format Firmware > Upgrade Download Stop D A DL All With Check Sum Download Agent D:/ \SP_Flash_Tool_v3.1248.0.96 (Pentru V100)\MTK_AllInOne_DA.bin Download Agent D:/ Download Down	Download Read b	ack Memory Test						
Download Agent D: \SP_Flash_Tool_v3.1248.0.96 (Pentru V100)\MTK_AllinOne_DA.bin Download A Scatter-loading File D: \S. (14.06.2013)\S80738_MP_F2F3F8_B188_R0_B0D_04_06_flasher_user\MT6577_Android_scatter Scatter-load Authentication File Firmware Upgrade Image: Certification File Cert File Nand Util File No00000000 0x00000000 0x00000000 0x00000000 Y PRELOADER 0x00000000 0x0000000 0x0000000 0x0000000 MBR 0x00000000 0x0000000 0x0000000 0x0000000 0x0000000 Y UBOOT 0x00000000 0x00000000 0x00000000 0x00000000 0x0000000 Y UBOOT 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 Y UBOOT 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 Y UBOOT 0x00000000 0x00000000 0x00000000 0x00000000 0x00000000 Y UBOOT 0x00000000 0x00000000 0x00000000 0x00000000	C Format	😨 Firmware -> Upgrade	ා Download	Ø Sto		NI With Check Sum		
Scatter-loading File D:\ \6. (14.06.2013)\S80738_MP_F2F3F8_B1B8_R0_B0D_04_06_flasher_user\MT6577_Android_scatter Image: Scatter-loading File Authentication File Image: Scatter-loading File Ima) ownload Agent	D:\	\SP_F	lash_Tool_v3.12	48.0.96 (Pentru V100)'	MTK_AllInOne_DA.bin		🗁 Download Agen
Authentication File	Catter-loading File	D:\	6. (14.06.2013)	S8073B_MP_F2F	3F8_B1B8_R0_B0D	_04_06_flasher_user\MT6577_Androi	d_scatter	🗁 Scatter-loading
Settification File Firmware Upgrade (B) Nand Util File Cert File PRELOADER 0x00000000 0x00000000 0x00000000 0x00000000 PSP_BL 0x000000000 0x00000000 0x00000000 0x00000000 0x00000000 MBR 0x00000000 0x000000000 0x000000000 <t< td=""><td>Authentication File</td><td></td><td></td><td></td><td></td><td>2</td><td></td><td>🗁 Auth File</td></t<>	Authentication File					2		🗁 Auth File
And Util File Image: Tegion address begin address end add ✓ PRELOADER 0x00000000000000000000000000000000000	Certification File			Firm	ware Upgrade 🗵			🗁 Cert File
name region address begin address end add ✓ PRELOADER 0x00000000000000000000000000000000000	Vand Util File							🗁 Nand Util File
	V PRELOADER V DSP_BL V MBR V EBR1 V UB00T B000TMG RECOVERY V SEC_R0 V LOG0 V ANDROID 4	0x000000000 0x000000000 0x00000000	0x0000000 0x0000000 0x0000000 0x0000000 0x00000000	0x00000 0x00000 0x00000 0x00000 0x000000	D:\TELEFOANE\VTI D:\TELEFOANE\VTI D:\TELEFOANE\VTI D:\TELEFOANE\VTI D:\TELEFOANE\VTI T	 IN6. (14.06.2013)/S00738_MP_F2F3 	3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_ 3F8_B1B8_	RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite RO_BOD_04_06_fite
		1			109	1)		
			DA DL AII W	thout Battery (F	ull Speed)			

9. Porniti telefonul, noua versiune Firmware a fost instalata cu succes.



Aceasta imagine este doar un exemplu, ecranul principal al telefonului poate fi diferit in functie de versiunea Firmware.

ATENTIE! Dupa ce ati efectuat procedura de update este foarte important sa dati un reset (revenire la setarile din fabrica). Intrati in meniul "Setari", "Creati o copie de rezerva si resetati", "Resetarea configurarii din fabrica", bifati optiunea "Stergeti cardul de stocare interna", apasati "Resetati tableta" apoi apasati "Stergeti tot".

- NOTA 1 Prima pornire a tabletei dupa update va necesita un timp mai indelungat, aveti rabdare si nu intrerupeti acest process.
- NOTA 2 La prima pornire a tabletei dupa update, este necesar sa o lasati sa se descarce complet (cu tableta pornita efectuand operatiunile obisnuite).
- **NOTA 3** In orice moment puteti reveni la versiunea de soft anterioara, este necesar sa urmati aceste instructiuni si sa folositi fila de update corespunzatoare.
- Evitati folosirea unui cablu USB sau a unui port USB de pe PC care prezinta probleme;
 Evitati sa folositi langa PC si tableta aparate electrocasnice ce produc perturbatii electromagnetice (aparat de uscat parul, cuptor cu microunde...etc);
 Indepartati din zona de lucru orice telefon mobil.